

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white & clear acrylic finish (white bezel included)
- Constructed from steel & aluminium alloy & polycarbonate
- CCT switchable - Three colour temperature to choose from: Warm White (3000K), Cool White (4200K) & Daylight White (6000K)
- Mains dimmable
- Loop-in / Loop-out detachable quick wire push-fit connector
- 30, 60 and 90 minutes fire rated
- Tested with insulation cover thickness 27cm
- IP65. Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD

SPEC DATA

| | |
|----------------------------|-----------------------|
| Product Wattage: | 7W |
| Product Lumen: | 800 |
| Lumen/W: | 114 |
| Kelvin: | 3000/4200/6000K |
| Energy Rating: | A++ |
| Dimmable: | Yes |
| Beam Angle: | 60° |
| Power Factor: | >0.85 |
| CRI: | >80 |
| Lifetime (Hours): | 30000 |
| LED Package: | San'an |
| SDCM: | <6 |
| Driver Type: | Constant Current 70mA |
| Product Voltage: | 220-240V |
| Hertz: | 50/60 |
| Surge Protection (KV): | 1 |
| Operating Temp.: | -20 to 40 Degree |
| Product Weight (KG): | 0.245 |
| Cut-out (mm): | Ø70mm |
| Minimum Cavity Depth (mm): | 50mm |
| Terminal Block: | Push-fit 6 ways |
| Class: | 2 |

ACCESSORIES

- 90377, Satin nickel bezel
- 90378, Polished chrome bezel

