

BF2440S. BF2440EMS Fusion 24W Round IP44 LED Luminaires c/w Microwave Sensor

Description	24Watt LED luminaire Opal diffuser c/w Microwave Sensor
Optional Trim Finishes available	BF24BBR – Matt Brass. BF24BCHR – Chrome.
•	BF24BMS - Matt Silver. BF24BWHT - White
Overall dimensions (mm)	(H)117mm (D)388mm (Without Bezel) (H)117mm (D)400mm (With Bezel)
Product Weight	BF2440S - 1.48kg BF2440EMS - 1.8Kg
Recommended product location	Indoor or Outdoor
Lamp Supplied	Yes 24W SMD LED Colour 6000K (BF24L6K) 30,000 hour
Voltage (V)	230V 50Hz
Running current (I)	0.11Amps
Lamp Wattage (W)	24Watts
Lumen Output	1600Lm – 66Lm/W
Dimmable	No
Class	Class II Must not be Earthed
IP	IP44
Distance from lighted object	1.0M
Photometric Testing	Yes
Power factor correction	Yes >0.93
Instruction sheet	Yes
Origin of manufacture	China
Main materials:	
Chassis	Polycarbonate
Body	Polycarbonate
Diffuser	Polycarbonate
Method of fix	Direct fixing – Screws provided
Lamp type and base	24W SMD LED Colour 6000K (BF24L6K) 4000K (BF24L4K)
Electrical Connections	10A Nylon Connector, Screw Terminals + Slave Terminal
Running Gear / Make	Knightsbridge LED Driver
	Operating Temperature - 20°C to +35°C
	Integral H.F. 3 hour Maintained emergency (BF2440EMS version)
MSENSOR	3600 Surface Microwave Sensor
Overall dimensions (mm)	Depth 40mm. Length 92mm width 42mm
Operating Type	Microwave Motion Sensor
Maximum Lamp Wattage (W)	1000Watt Incandescent or 500W Fluorescent
Operating Light Levels	User Adjustable 2 – 2000lux
Operating Time Levels	User adjustable Min - 3 Seconds Max – 30 Minutes
Detection Range	2 - 8 metres
Detection Angle	360°
F mark	Yes
CE mark	Yes
Quality Assurance System	Yes ISO 9001 QMS
Batch coding on product	Yes
Certificate of Conformity	Yes
Manufactured in accordance to:	EN60598
Guarantee Period	3 Year
EAN	BF2440S -5055559190776 BF2440EMS - 5055559190790