

IP65 LED Floodlight



| MLA part code | FLF10M | FLF20M | FLF30M | FLF50M | FLF80M |
|--|--|--|--|---|---|
| Description | LED floodlight | | | | |
| Finishes | Black | | | | |
| Net weight (kg) | 0.474 | 0.683 | 0.9 | 1.715 | 3.626 |
| Wattage (W) | 10 | 20 | 30 | 50 | 80 |
| Overall dimensions (mm) | Length: 130 Height: 90 Projection: 80 | Length: 180 Height: 126 Projection: 87 | Length: 210 Height: 147 Projection: 95 | Length: 260 Height: 182 Projection: 106 | Length: 360 Height: 254 Projection: 140 |
| Lumen Output (lm) | 1150 | 2240 | 3100 | 5380 | 7740 |
| Efficacy (lm/W) | 115 | 112 | 103 | 107 | 96 |
| ErP Class | A++ | A+ | A+ | A+ | A+ |
| Operating current (A) | 0.079 | 0.118 | 0.148 | 0.233 | 0.351 |
| P.F | 0.7 | >0.8 | >0.9 | >0.9 | >0.9 |
| CCT | 4000K | | | | |
| LED Colours | Cool white | | | | |
| CRI | >70 | | | | |
| Input voltage | Mains 230V 50Hz | | | | |
| Construction | Die cast Aluminium | | | | |
| Class | Class I | | | | |
| IP rating | IP65 | | | | |
| Sensitivity | 1 to 8m (in ideal conditions and mounted at 2.4m high) | | | | |
| Time duration | 5s to 24hrs | | | | |
| Manual override | Yes | | | | |
| Life span | 30,000 hrs | | | | |
| Pre Wired | Yes with 1m cable | | | | |
| Warranty | 3 Years | | | | |
| Additional accessories | FLFR - sensor remote control (sold separately) | | | | |
| Dimmable | No | | | | |
| Origin of Manufacture | China | | | | |
| Quality assurance system | ISO9001 | | | | |
| Declaration of Conformity (held on file) | Yes | | | | |
| Manufactured in accordance with | BS EN60598 | | | | |
| EAN | 5055832947035 | 5055832947332 | 5055832947486 | 5055832947578 | 5055832947653 |

