



DATASHEET



IC Fire Rated IP65 Downlight with Variable Wattage and CCT

For 5W

For 8W



| MLA PART CODE | SPEK2W4CCT | | | | | | | |
|--|--|-------|-------|-------|-------|-------|-------|-------|
| DESCRIPTION | IC Fire Rated IP65 Downlight with Variable Wattage and CCT | | | | | | | |
| FINISH | Black | | | | | | | |
| NETT WEIGHT (Kg) | 0.23 | | | | | | | |
| DIMENSIONS (mm) | Diameter – 87 Projection – 4 Recessed depth – 42 | | | | | | | |
| CUT-OUT (mm) | 70 | | | | | | | |
| MINIMUM VOID (mm) | 42 | | | | | | | |
| WATTAGE (W) | 5 | | | | 8 | | | |
| CCT | 2700K | 3000K | 4000K | 6000K | 2700K | 3000K | 4000K | 6000K |
| LUMENS (±5% lm) | 440 | 445 | 465 | 450 | 750 | 745 | 740 | 795 |
| EFFICACY (lm/W) | 93.9 | 96.4 | 103.7 | 98.2 | 95.7 | 98 | 98.6 | 101.8 |
| CRI | >80 | | | | | | | |
| CIRCUIT WATTAGE (W) | 4.6 | | | | 7.9 | | | |
| RUNNING CURRENT (A) | 0.029 | | | | 0.041 | | | |
| POWER FACTOR | 0.7 | | | | 0.8 | | | |
| BEAM ANGLE | 60° | | | | | | | |
| LIFE SPAN (HRS) | 50,000 Hrs | | | | | | | |
| FIRE RATING (I-JOIST) | 30 min. | | | | | | | |
| FIRE RATING (SOLID WOOD JOIST) | 30/60/90 min. | | | | | | | |
| FIRE RATING (WEB JOIST) | 30 min. | | | | | | | |
| INPUT VOLTAGE | Mains 230V 50Hz | | | | | | | |
| AMBIENT TEMP | -25° ~ +40°C | | | | | | | |
| CONSTRUCTION | Pressed Steel | | | | | | | |
| CLASS | Class II | | | | | | | |
| IP RATING | IP65 (IP20 from above) | | | | | | | |
| DIMMABLE | Yes, with most trailing edge dimmers | | | | | | | |
| WARRANTY | 5 Years | | | | | | | |
| ORIGIN OF MANUFACTURE | China | | | | | | | |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes | | | | | | | |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 | | | | | | | |
| EAN | 5056270826241 | | | | | | | |

