



PLED5W & PLED9W Recessed LED Luminaire

Description	Recessed 5W LED fitting	Recessed 9W LED fitting
Overall dimensions (mm)	Dia-140mm Depth-24mm	Dia-180mm Depth 23.5mm
Cut-out	125mm	165mm
Wattage	5W	9W
Circuit Watts	5W	9W
Lumen Output	300Lm	590Lm
Voltage	230V 50Hz	
Recommended product location	Indoor	
Finishes available	White – Opal Diffuser	
Output Colour	4000K Cool White	
Average Lamp Life	30,000 hours	
Control Gear Type	Built in driver	
Dimmable	No	
Lamp Supplied	Yes – Non replaceable LED	
Class	Class II.	
IP	IP20	
Photometric Testing	Yes	
Instruction sheet	Yes	
Origin of manufacture	China	
Main materials:		
• Chassis	Polycarbonate	
• Diffuser	Opal Polycarbonate	
Method of fix	Twin spring clips	
Lampholder cap and make	N/A – Non replaceable lamps	
Electrical Connections	Pre wired 500mm 2 core 0.75mm ² flex	
CE mark	Yes	
Quality Assurance System	Yes ISO 9001 QMS	
Batch coding details on product	Yes	
Certificate of Conformity (Held on File)	Yes	
Manufactured in accordance	EN60 598	

ML Accessories Ltd. reserves the right to withdraw, improve or modify any design without prior notification.

ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.