



DATASHEET



LED IP65 8W Fire-Rated Downlight 4000K



DESCRIPTION	LED IP65 8W Fire-Rated Downlight 4000K
NET WEIGHT (KG)	0.207
DIMENSIONS (MM)	Diameter - 80 Projection - 3.8 Recessed Depth - 41 Minimum Void - 97
CUT-OUT (MM)	Cut-out Diameter - 64
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	8
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	690
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	80.62
CIRCUIT WATTAGE (W)	8.57
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.039
BEAM ANGLE (DEGREES)	40
LIFE SPAN (HRS)	35,000
DIMMABLE	Yes*
EMERGENCY CONVERSION KIT	VFR7EM
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
IC RATED	No
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 8WW OUTPUT VOLTAGE - 30-38vV OUTPUT CURRENT - 180mA
WARRANTY	4year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055559197935