

GENERAL

| | |
|---------------------------|---------------------|
| LOCATION: | Interior |
| CLASS: | CE (Class I) |
| IP RATING: | IP20 |
| BATHROOM ZONE: | Zone 3 |
| DRIVER REQUIRED: | No |
| INSTALLATION ORIENTATION: | Wall Mount |
| MAIN MATERIAL: | Metal - Zinc |
| DIMENSIONS (mm): | H: 225 W: 80 D: 144 |
| CUT OUT HOLE : | - |
| RECESS DEPTH (mm): | - |
| FIRE RATING: | - |
| CABLE LENGTH (mm): | - |
| GROSS WEIGHT (kg): | 1.09 |

LAMP

| | |
|--------------------------------|------------------|
| LIGHT SOURCE: | High Powered LED |
| WATTAGE: | 4.1W |
| LAMP INCLUDED: | Yes (Integral) |
| MAXIMUM LAMP LENGTH (mm): | - |
| LUMINOUS FLUX (lm): | 149 |
| COLOUR TEMP (K): | 2700 |
| CRI (Ra): | 90 |
| MACADAM ELLIPSE: | 3-Step |
| TILT ADJUSTABLE ANGLE (°): | 90 |
| ROTATION ADJUSTABLE ANGLE (°): | 330 |
| LIFETIME (hrs): | 60000 |
| BEAM ANGLE (°): | 17 |

ELECTRICAL


| | |
|-----------------------------|---------|
| SWITCHED: | Yes |
| DIMMABLE: | No |
| DIMMING METHOD: | - |
| SUPPLY FREQUENCY (Hz): | 50-60 |
| DRIVER/BALLAST VOLTAGE (V): | 100-277 |
| DRIVER LIFETIME (hrs): | 30000 |
| EFFICACY (lm/W): | 36 |

ADDITIONAL INFORMATION:

| | |
|--------------------------|---|
| SHADE INCLUDED: | - |
| SHADE/DIFFUSER MATERIAL: | - |
| SHADE/DIFFUSER FINISH | - |
| F MARK: | Suitable for mounting on flammable materials |



CODE: 1058153
FINISH: MATT BLACK



CODE: 1058154
FINISH: MATT WHITE



CODE: 1058155
FINISH: MATT NICKEL



CODE: 1058156
FINISH: MATT GOLD

