

## Bellhop Wall Non Dimmable

■ F003C31A056 - Matte Stainless Steel




Designed by Edward Barber and Jay Osgerby

Wall light version of the Bellhop Outdoor Collection for diffuse light, made of extruded and die-cast aluminium or stainless steel.

100-240V power supply integrated. Direct wall installation.

Each luminaire is equipped with 200 mm length cable for connection inside the luminaire body.

Recommended connection with a 2 way terminal block 4 poles IP68 H2O Stop, to be ordered separately.




### Main specifications

|                                 |   |                           |     |
|---------------------------------|---|---------------------------|-----|
| <b>Mounting</b>                 | Wall  | <b>Ilcos</b>              | No  |
| <b>Environment</b>              | Outdoor wet location                                  | <b>Dimmable</b>           | No  |
| <b>Light source replaceable</b> | Replaceable (LED only) light source by a professional | <b>Autoprotected Lamp</b> | No  |
| <b>LED type</b>                 | Power LED   | <b>Source Power (W)</b>   | 8   |
| <b>Lamp category</b>            | LED   | <b>System Flux (lm)</b>   | 580 |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting Type</b>          | Direct    |
| <b>Lighting distribution</b>  | Symmetric |
| <b>CCT (K)</b>                | 3000      |
| <b>CRI &gt;</b>               | 80        |
| <b>Cold Beam Lighting</b>     | No        |
| <b>Beam angle C0-180 (°)</b>  | 85        |
| <b>Beam angle C90-270 (°)</b> | 85        |
| <b>Extreme Cut off</b>        | No        |



Luminous flux luminaire  
580 lm

### Electrical

|                           |            |                                 |  |
|---------------------------|------------|---------------------------------|--|
| <b>Insulation class</b>   | I          | <b>Dimmable type</b>            | Non Dimmable                               |
| <b>Frequency (Hz)</b>     | 50-60      | <b>Power supply replaceable</b> | Replaceable control gear by a professional |
| <b>Main Voltage (Vac)</b> | 220-240    | <b>Emergency Type</b>           | No   |
| <b>Driver</b>             | Integrated |                                 |  |
| <b>Dimmable</b>           | No         |                                 |  |

### Physical

|                        |                       |
|------------------------|-----------------------|
| <b>Colour</b>          | Matte Stainless Steel |
| <b>Trim</b>            | No                    |
| <b>Orientations</b>    | Fixed                 |
| <b>Net weight (kg)</b> | 1.1                   |
| <b>IP</b>              | 65                    |

### Note

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.




## Bellhop Wall Non Dimmable



---

2 way terminal block 4  
poles IP68 H20 stop.  
( $\varnothing 5,5 \div 12\text{mm}$  cable)  
F990C00A000



---

S.P.D. (SURGE  
PROTECTION DEVICE)  
F990E00A000